## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization International Bureau





## (43) International Publication Date 6 September 2002 (06.09.2002)

### **PCT**

# (10) International Publication Number WO 02/068205 A1

(51) International Patent Classification7:

\_\_\_\_

B41M 5/26

(21) International Application Number: PCT/GB02/00862

(22) International Filing Date: 27 February 2002 (27.02.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0104959.2 0114977.2 28 February 2001 (28.02.2001) GB 19 June 2001 (19.06.2001) GB

(71) Applicant (for all designated States except US): SHER-WOOD TECHNOLOGY LTD. [GB/GB]; Heathcoat Building, Nottingham Science & Technology Park, University Boulevard, Nottingham NG7 2QJ (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KHAN, Nazir [GB/GB]; Sherwood Technology Ltd., Heathcoat Building, Nottingham Science & Technology Park, University Boulevard, Nottingham NG7 2QJ (GB). (74) Agent: GILL JENNINGS & EVERY; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LASER CODING

(57) Abstract: A method for marking an object, wherein the object comprises a material including a functional group and a metal compound or acid that causes an elimination reaction on irradiation with a laser, to form a reaction product of contrasting colour, comprises directing a laser beam on to the areas of the object to be marked. For example, by using a carbohydrate and a metal salt, effective marking can be achieved on the coating of a pill or other edible material.



10

15

20

25

### LASER CODING

### Field of the Invention

This invention relates to laser coding, particularly of edible materials.

## Background of the Invention

Laser coding is well known; see, for example, US-A-5783793, US-A-4906813 and also US-A-5340628 which seeks to contain the particles produced by ablation. These methods present a variety of problems, including difficulties in maintenance, line down-time, taint, as well as the need for extraction. More generally, the apparatus and problems of printing, i.e. ribbons, inks, solvents, maintenance, unreliability, etc., are particularly undesirable where sensitive products like foods and pharmaceuticals are packaged.

Various proposals have been made, in order to achieve effective printing without ablation, and without applying ink at the point of coding, but rather by causing a change of colour in the substrate on which the printing is to appear. Various pigments have been proposed, which can be used to mark a substrate on the application of laser energy. Some of these proposals may be found in, for example, WO-A-00/43456, JP-A-11001065, EP-A-0522370, EP-A-0797511, US-A-5053440, US-A-5350792 (a plastic moulding composition comprising a polyoxymethylene and animal charcoal), US-A-5928780, US-A-6017972 and US-A-6019831.

On-line coding methods commonly used for the pharmaceutical, foods and confectionery industries are ink-jet and thermal transfer (including hot stamping).

## Summary of the Invention

The present invention is based on the utility of particular materials which can undergo a colour change on the application of laser energy, and the realisation that these include edible materials which can therefore be used to mark materials intended for consumption.

According to this invention, a method for marking an object, wherein the object comprises a material including a functional group and a metal compound or acid that causes an elimination reaction on irradiation with a laser, to form a

10

15

20

25

30

reaction product of contrasting colour, which comprises directing a laser beam on to the areas of the object to be marked.

Depending on the nature of the components that are used, and the reaction product, they may be physiologically acceptable. This means that the invention can be used in the making of foodstuffs and pharmaceutical products such as tablets and pills.

The method of the present invention overcomes the problems associated with printing, as described above. It allows significant cost savings for most normal production lines, and the opportunity to improve on the quality of the coding produced on foodstuffs and other products. Further advantages of the invention are that it can be highly reliable, involves low maintenance costs, and avoids solvents, emissions, debris and extraction. The invention provides online, non-contact coding, with reduced line down-time. The method of the invention can be used to replace all current coding systems, at the highest line speeds. There is no need for the purchase or stocking of materials associated with printing, and yet the quality of print can be improved. Adhesion problems and smudging can be avoided. There is no need to pierce wrapping film. Further, it is possible to code in damp conditions.

## Description of the Invention

In accordance with the invention, suitable additives are provided in a coating on a solid substrate, e.g. foodstuff, including confectionery, or pharmaceutical dosage units such as a tablet or pill. Such coatings are known, and may simply be modified according to the invention by inclusion of materials which react with each other, essentially to form a dye or chromophore *in situ*. The product is intended for consumption or (if pharmaceutical) oral administration, in which case the additive(s) and any reaction product are edible.

In one embodiment of this invention, the additives are a polyhydroxy compound and a dehydrating agent. The latter is typically a metal salt of the type that, as is known, can be used to remove OH groups (which for the purposes of this specification are functional groups) from sugars, e.g. sucrose, starches, modified starches, cellulose, modified celluloses, etc. Examples of suitable metal salts are alkali metal, alkaline earth metal, iron oxide/salts and

organometallics. Thus, for example, when heated by the application of laser energy, sucrose in the presence of MgO or FeO etc. will char. Other examples of materials that will give a colour change by dehydration (elimination of water) in the presence of a metal salt include:

5 Hydroxypropylcellulose

Methylhydroxypropylcellulose

Sodium carboxymethylcellulose

Polyvinyl alcohol

Suitable metal salts for this purpose include:

10 MgCl<sub>2</sub>

Mg(OH)<sub>2</sub>

CaO

FeO

Fe<sub>2</sub>O<sub>3</sub>

15 CaSiO₃

Zn acetate

ZnO

alumino-silicates

In a further embodiment of the invention, the elimination reaction may comprise dehalogenation, dehydrohalogenation or deacetylation, in which case the relevant functional group is a halogen atom or carboxyl group. Examples of additives for this purpose are vinyl polymers, typically in the present of a metal salt. Suitable polymers include:

Polyvinyl chloride (PVC)

25 Polyvinyl acetate

Vinyl esters

Vinyl chloride/acetate copolymer

Vinyl chloride/maleate copolymer

Suitable metal compounds for this purpose include:

30 ZnO

Zn salicylate

Kaolin

CaSiO<sub>3</sub>

10

15

20

25

30

Yet another embodiment of the invention uses additives that undergo deetherification. Thus, for example, ethyl cellulose and a metal salt will give a colour on irradiation.

The examples given above are primarily of metal salt-induced elimination. A further embodiment of the invention is acid or base-induced dehydration/dehalogenation/dehydrohalogenation/deacetylation/deetherification. Thus, for example, a colour is generated using p-toluenesulphonic acid with PVOH (polyvinyl alcohol).

Based on this information, other suitable materials will be known, or can be readily chosen or tested for their suitability, by those of ordinary skill in the art.

A particular advantage of the invention is that the object to be marked may be pre-wrapped, provided that the wrapping is transparent to the applied energy; in other words, film-wrapped tablets or other such products can be printed by means of the present invention. Many commonly available wrapping films have been found to be transparent to IR laser energy, including PE, PP, PET, PVC, cellulose and cellulose acetate.

As indicated above, the or each additive may be responsive to UV or IR radiation, and any suitable materials may be used, provided that they can produce a colour change. The change may be due to the material undergoing chemical or physical change as a result of the absorption of laser energy, or as a result of that energy being converted to thermal energy. Thus, for example, polyvinyl alcohol is known as a coating ingredient; if a dehydrating agent such as p-toluenesulphonic acid is included in the coating, the application of energy can lead to conjugation and a colour change. Further examples of suitable materials include carbohydrates that can be caramelised, and a combination of ethylcellulose with calcium hydroxide. Preferably, the additive or an existing component will strongly absorb the radiation.

The space allocated on a package for the batch code, sell-by date, etc. is usually a small patch printed in a light colour to give good contrast to the (normally) black print. Using the system of the invention, this may be a white or lightly-coloured patch, which is printed with a laser-sensitive ink. On exposure

10

15

25

30

to a threshold dose of laser energy, the ink changes colour to give the code. The patch may be printed down by a known printing technique, e.g. by flexo or gravure, as the packaging is made.

The object to be marked may be formulated with the additional components that allow marking. In a preferred embodiment, these components are formulated and used to coat a substrate. For application to the substrate, the material or materials used in this invention may be formulated in an aqueous or non-aqueous system, as a solution or dispersion. For coating on pills, the transparency of the coating is not usually a consideration, but the use of a solution of components may be preferred, in order to provide a clear coating on certain substrates. Since it may determine the clarity of the marking that can be achieved, coating may be done more than once, if desired.

The amounts of the components that are used in the invention can readily be chosen by one of ordinary skill, having regard to the intended use. For example, a coating composition may comprise 0.1 to 20% w/v of each component.

It has been demonstrated that, in accordance with the invention, single or multiple layers of water-based edible laser-scribable coatings can be applied to unpolished or polished tablets by a conventional tablet coating process. On top of the coating, a layer of the carnauba wax can be applied by a conventional coating process without any difficulty.

Tablets coated with three or more layers of the water-based edible coatings are markable with CO<sub>2</sub> laser and afford good quality grey/green laser marking. The coatings are laser-markable through the layer of carnauba wax.

Typically, the necessary energy will be a laser beam. For example, a print engine for an IR coding system comprises a robust, low-power CO<sub>2</sub> laser, e.g. operating at about 10,600 nm. The laser can operate in either the dot matrix mode or continuous-wave, scribing mode. In this latter mode, improved quality of print can be obtained. Because of the low output of the laser, highly reliable, approaching maintenance-free, operation is offered. The system can operate in a scribe mode, and coding onto moving lines at up to 200 m/min is possible. For higher speeds than this, dot matrix printing is suitable.

The system can be used for coding through packing film, or coding into film laminates. A low-power laser ensures that puncturing does not occur.

The following Examples illustrate the invention.

## Examples 1 to 12

Materials etc are shown in the following Table. Those of Examples 9 to 12 are particularly suitable for use as an edible composition.

In each case, a lacquer was mixed, coated and dried before marking with a CO<sub>2</sub> laser, using a beam of 0.3 mm diameter and scan speed of 1000 mms<sup>-1</sup>. Vinnol is a vinyl chloride/acetate copolymer supplied by Stort Chemicals. Vycar is a copolymer of vinyl chloride and an acrylic acid supplied by Goodrich.

Colour of Image	Black	Black	Black		Black		Yellow	Black	Black	Yellow	Yellow	Yellow	Yellow	Yellow
Laser Power (W)	5	6-7	5-6		5-6	·	5-6	5-6	5-6	3	5-6	5-G	6-7	O
Quantity (g)	80	10	9		ဖ		5	10	9	4.8	15	10	15	9
Solvent	MEK	MEK	MEK		MEK		MEK	MEK	MEK	Water	Water	Water	Ethanol	Water
Quantity (g)	0.5	1	0.3	0.2	0.3	0.3	0.3	-	1	1	-	-	-	-
Additive	Zinc chloride	Zinc oxide	Zinc oxide	Calcium silicate	Zinc oxide	Kaolin	Calcium silicate	Zinc 3,5-di-tert butyl salicylate	Irgacure 261	Zinc Oxide	Magnesium chloride	Magnesium chloride	Calcium hydroxide	Calcium hydroxide
Quantity (9)	22	L	ဧ	<u> </u>	င	<u> </u>	2	4	က	10	2	-	2	1.5
Binder	Vinnol 14/36	Vinnol 14/36	Vinnol 14/36		Vinnol 14/36		Vinnol 14/36	Vinnol 14/36	Vinnol 14/36	Vycar 577-E	Klucel (hydroxy propyl cellulose)	Culminal (methyl hydroxy propyl cellulose)	Ethyl cellulose	Blanose (sodium carboxy methyl cellulose)
Example	-	2	·w		4		5	9	7	80	6	5	7	12

10

15

## Example 13

100 g sodium carboxymethylcellulose was added portionwise to 2000 g water, with stirring. Once the addition was complete, stirring was continued until complete dissolution of the polymer was achieved.

100 g MgCl<sub>2</sub>.6H<sub>2</sub>O was added portionwise to the polymer solution. After the addition was complete, the mixture was stirred for approx. 10 min, to give a coating solution.

2 kg tablets were charged into a coating pan. The coating pan containing the tablets was rotated at constant speed, and then the tablets were warmed up to 50°C using a hot air dryer.

For a first coating layer, 10 ml of the coating solution was added and the coating pan was allowed to rotate at constant speed and ambient temperature for approximately 10-15 minutes. The coated tablets were warmed to approximately 50°C with a hot air dryer whilst the pan was rotated at constant speed. A 200 g sample of the coated tablet was taken. Using two more 10 ml volumes of the coating solution, the coating procedure was repeated twice.

Laser marking of the coated tablets was investigated using a 10 W Alltec CS smart carbon dioxide laser. Parameters used for the marking of the tablets are presented below:

20

Laser frequency	20000 Hz
Power	7 Watts
Scan velocity	500 mm/sec
Line width	50 µm
Lens	200 mm

25

30

A reasonable dark grey/green image was obtained.

## Example 14

The procedure of Example 13 was repeated, except that the tablet was polished, i.e. a final coat of wax was applied by the addition of 805 mg of a 50% ethanolic solution of carnauba wax to the coating pan. Again, a reasonable dark grey/green image was obtained. The same result was obtained if the tablet was

polished underneath, i.e. if the coating of laser-sensitive material was on top of a coating of carnauba wax.

### Example 15

5

10

The procedure of Example 13 was repeated, but using a solution obtained from 30 g sodium carboxymethylcellulose, 30 g MgCl<sub>2</sub>.6H<sub>2</sub>O and 400 g water. A good grey/green image was obtained, with or without polishing (as described in Example 14).

## Example 16

The procedure of Example 13 was repeated, but using a coating solution obtained by adding 750 g Vinnol 14/36 portionwise to 1500 g 2-butanone (MEK) with stirring, until the addition is complete, followed by stirring until dissolution of the polymer is complete, followed by the addition of 150 g zinc oxide portionwise with stirring, and for 30 minutes after addition is complete, to disperse the zinc oxide uniformly. Laser marking gave a dark black image.

### **CLAIMS**

5

- 1. A method for marking an object, wherein the object comprises a material including a functional group and a metal compound or acid that causes an elimination reaction on irradiation with a laser, to form a reaction product of contrasting colour, which comprises directing a laser beam on to the areas of the object to be marked.
- 2. A method according to claim 1, wherein the material is polymeric and undergoes deetherification, dehalogenation, dehydrohalogenation or deacetylation in the present of a metal salt or acid.
- 10 3. A method according to claim 2, wherein the material undergoes dehalogenation.
  - 4. A method according to any preceding claim, wherein the material is a vinylic polymer.
- A method according to claim 4, wherein the vinylic polymer is polyvinyl
   chloride, polyvinyl acetate, a vinyl ester, a vinyl chloride/acetate copolymer or a vinyl chloride/maleate copolymer.
  - 6. A method according to any preceding claim, wherein the metal compound is a salt, oxide or silicate.
- 7. A method according to claim 1, wherein the material is a polyhydroxy compound and the elimination occurs in the presence of an acid or metal salt.
  - 8. A method according to claim 7, wherein the polyhydroxy compound is a carbohydrate.
  - 9. A method according to claim 7, wherein the polyhydroxy compound is cellulosic.
- 25 10. A method according to any preceding claim, wherein the object is a pharmaceutical or foodstuff, and the reaction product is physiologically acceptable.
  - 11. A method according to any preceding claim, wherein the object comprises a substrate and, coated thereon, a coating comprising the polymeric material and the metal compound.
  - 12. A method according to claim 11, wherein the is a tablet or pill and the substrate comprises a pharmaceutical agent.

30

- 13. A method according to any preceding claim, wherein the object is wrapped or covered in a filmic material.
- 14. A coating composition comprising a solution or dispersion of a polymeric material and a metal compound as defined in any of claims 1 to 10.
- 5 15. A composition according to claim 14, which is aqueous.

## INTERNATIONAL SEARCH REPORT

ial Application No PCT/GB 02/00862

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 B41M5/26

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols) IPC 7 **B41M** 

Documentation searched other than minimum documentation to the extent that such documents are included. In the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

PAJ, WPI Data, EPO-Internal, IBM-TDB, CHEM ABS Data, PAPERCHEM, PIRA

Category °	ENTS CONSIDERED TO BE RELEVANT  Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
X	EP 0 327 508 A (CIBA-GEIGY AG) 9 August 1989 (1989-08-09) page 2, line 1 - line 6 page 2, line 47 - line 53 page 3, line 28 - line 31 page 3, line 55 - line 62 claims 1-3,11	1-15		
X	EP 0 782 933 A (NIPPON KAYAKU K.K.) 9 July 1997 (1997-07-09) column 1, line 52 -column 2, line 13 column 3, line 15 - line 17 column 4, line 55 -column 5, line 30 column 6, line 22 claims 1,4	1-15		

Further documents are listed in the continuation of box C.	Patent family members are listed in annex.				
Special categories of cited documents:  'A' document defining the general state of the art which is not considered to be of particular relevance  'E' earlier document but published on or after the International filing date  'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  'O' document referring to an oral disclosure, use, exhibition or other means  'P' document published prior to the international filing date but later than the priority date claimed	<ul> <li>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</li> <li>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</li> <li>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</li> <li>"&amp;" document member of the same patent family</li> </ul>				
Date of the actual completion of the international search  15 May 2002	Date of mailing of the International search report  27/05/2002				
Name and mailing address of the ISA  European Patent Office, P.B. 5818 Patentlaan 2  NL – 2280 HV Rijswijk  Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  Fax: (+31-70) 340-3016	Authorized officer Bacon, A				

Form PCT/ISA/210 (second sheet) (July 1992)

### INTERNATIONAL SEARCH REPORT

	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	Relevant to claim No.
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Helevani to claim No.
X	EP 0 708 147 A (JAPAN SYNTHETIC RUBBER COMPANY LIMITED) 24 April 1996 (1996-04-24) page 2, line 20 - line 41 page 7, line 53 - line 57 claim 1	1-6, 11-15
X	EP 0 841 187 A (BAYER AG) 13 May 1998 (1998-05-13) page 2, line 1 - line 45 page 5, line 31 - line 42 page 6, line 14 - line 22 claims 1-3	1-6, 11-15
	·	

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

## INTERNATIONAL SEARCH REPORT

Inte ial Application No
PCT/GB 02/00862

Patent document cited in search report		Publication date		Patent family member(s)	Publication date	
EP 327508	Α	09-08-1989	EP JP	0327508 A2 2004584 A	09-08-1989 09-01-1990	
EP 782933	Α	09-07-1997	EP JP US	0782933 A1 9248968 A 5897938 A	09-07-1997 22-09-1997 27-04-1999	
EP 708147	Α	24-04-1996	JP JP DE DE EP US	3024495 B2 8120133 A 69503861 D1 69503861 T2 0708147 A1 5760120 A	21-03-2000 14-05-1996 10-09-1998 21-01-1999 24-04-1996 02-06-1998	
EP 841187	Α	13-05-1998	DE EP JP	19645940 A1 0841187 A1 10140017 A	14-05-1998 13-05-1998 26-05-1998	

Form PCT/ISA/210 (patent tamily annex) (July 1992)